

SDS

Solar Chemical 1234YF Arctic Air

1	PRODUCT AND COMPANY IDENTIFICATION
Product Identifier:	Solar Chemical 1234YF Arctic Air
Revision Date:	6/7/2022
Version:	1.0
Product Use:	Boost A/C Cooling Performance
Supplier Details:	Solar Chemical
	3741 Atlanta Industrial Parkway
	Atlanta, GA 30331
	Office: (404) 699-8766
Contact:	Roen Sanders
Phone:	(404) 699-8766
Email:	solarchem@atlanticchemical.com
Internet:	www.solarchemonline.com
Emergency Telephone:	Chemtrec 1-800-424-9300 (USA)

HAZARDS IDENTIFICATION

Classification of Substance

2

3

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Gases, 1 Physical, Gases Under Pressure, Compressed Gas

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

OSHA-H01 - May displace oxygen and cause rapid suffocation

GHS Precautionary Statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
- P381 In case of leakage, eliminate all ignition sources.
- P403 Store in a well-ventilated place.

P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:				
CAS#	%	Chemical Name:		
68476-85-7		Petroleum gases, liquefied		
64742-52-5		Distillates, petroleum, hydrotreated heavy naphthenio		



Solar Chemical 1234YF Arctic Air

Solar Chemical 1234YF Arctic Air FIRST AID MEASURES

Inhalation:	When symptoms occur: go inot open air and ventilate suspected area. Immediately call a POISON CENTER or doctor/physician.
Skin Contact:	If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.
Eye Contact:	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms/Injuries: Gas can be toxic as simple asphyxiant by displacing oxygen from the air. Refrigerated liquefied gas. Contact with product may cause cold burns or frostbite.

Symptoms/Injuries After Inhalation: Asphyxiate gas.

Symptoms/Injuries After Skin Contact: May cause frostbite. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Contact with the liquefied gas causes frostbite.

Symptoms/Injuries After Ingestion: Ingestion is an unlikely route of exposure for a gas.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

FIRE FIGHTING MEASURES

5.1. Extinguishing Media

5

6

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy water stream may spread fire.

5.2. Special Hazards Arising from the Substance or Mixture

Fire Hazard: Flammable gas.

Explosion Hazard: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Contains gas under pressure; may explode if heated. Reacts with strong oxidants causing fire and explosion hazard.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including repiratory protection.

ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Do not get ineyes, on skin, or on clothing.

6.1.1. No Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Eliminate ignition sources.

6.1.2. For Emergency Responders

Protective Equipment: Equip clean up crew with proper protection.

Emergency Procedures: Stop Leak if safe to do so. Ventilate area.

- 6.2. Environmental Precautions
- Avoid release to the environment

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Stop leak without risks if possible. Do not take up in combustible material such as: sa dust or cellulosic material.

Methods for CLeaning Up: Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.



SDS

Solar Chemical 1234YF Arctic Air

7	HANDLING AND STORAGE
Handling Precautions:	 7.1. Precautions for Safe Handling Precautions for Safe Handling: Personnel should be trained to regularly inspect equipment such as pumps, hoses, and valves. Do not breathe gas. Ensure there is adequate ventilation. Close valve after each use and when emptyl Open valve slowly to avoid pressure shock. Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.
Storage Requirements:	 7.2. Conditions for Safe Storage, Including Any Incompatibilities Technical Measures: Comply with applicable regulations. Keep at temperatures below 52C/125F. Storage Conditions: Store in a dry, cool and well-ventilated place. Keep in fireproof place. Store locked up. 7.3. Specific End Use(s): Boost A/C Cooling Performance
8	EXPOSURE CONTROLS/PERSONAL PROTECTION
Engineering Controls:	Alarm detectors should be used when toxic gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.
Personal Protective Equip	Petroleum gases, liquefied cas#:(68476-85-7)
	Gas mask. Protective goggles. Gloves. Protective clothing.
	Materials for Protective Clothing: Chemically resistant materials and fabrics. Hand Protection: Wear working gloves when handling gas containers. Eye Protection: Safety glasses. Skin and Body Protection: Wear suitable protective clothing. Respiratory Protection: use a NIOSH-approved self-contained breathing apparatus in oxygen deficient atmospheres. Thermal hazard Protection: Wear cold insulating gloves.

Petroleum gases, liquefied cas#:(68476-85-7)

USA ACGIH - ACGIH TWA (ppm): 1000ppm USA NIOSH - NIOSH REL (TWA) (mg/m3): 1800mg/m3 USA NIOSH - NIOSH REL (TWA) (ppm): 1000ppm USA IDLH - US IDLH (ppm): 2100ppm (10% LEL) USA OSHA - OSHA PEL (TWA) (mg/m3): 1800mg/m3 USA OSHA - OSHA PEL (TWA) (ppm): 1000ppm

9	PHYSICAL AND CHEMICAL PROPERTIES			
Appearance:	Clear, colorless gas			
Physical State:	Gas	Odor:	No data available	
Odor Threshold:	No data available	Solubility:	No data available	
Specific Gravity or Densit	y: .540	Freezing or Melting Point:	-166 °C (-267.1 °F)	
Viscosity:	No data available	Flash Point:	-104 °C (-155 °F)	
Boiling Point:	-34.7 °C	Vapor Density:	1.76	
Partition Coefficient:	< 1	Autoignition Temperature:	862.8 °C (1585 °F)	
Vapor Pressure:	70 @ 21.1 °C	Upper Flammability Limit and Lower Flammability Limit:	8.5 % / 1.9 %	
Potentia Hydrogenii:	No data available			
Evaporation Rate:	Rapid			
Decompression Temperature:	No data available			



Solar Chemical 1234YF Arctic Air

10 STABILITY AND REACTIVITY

Reactivity: Chemical Stability: Conditions to AvoIdentification: Materials to AvoIdentification: Hazardous Decomposition: Hazardous Polymerization: Contains gas under pressure; may explode if heated. Reacts with oxidants causing fire and explosion hazard. Stable under recommended handling and storage conditions Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks. Strong oxidizing agents. Carbon oxides Will not occur

11

TOXICOLOGICAL INFORMATION

Petroleum gases, liquefied cas#:(68476-85-7)

Information on Toxicology Acute Toxicity: Not classified LC50 Inhalation Rat: 658mg/l/4h Petroleum Oil: > 2000 mg/kg LD 50 Oral Rat: > 2000 mg/kg LD50 Dermal Rat: > 2000 mg/kg LC50 Inhalation Rat: > 2000 mg/kg

Skin Corrosion/Irritation: Not classified Serious Eye Damage/Irritation: Not classified Respiratory or Skin Sensitiation: Not classified Germ Cell Mutagenicity: Not classified Carcinogenicity: Not classified Reproductive Toxicity: Not classified Specific Target Organ Toxicity (Single Exposure): Not classified Specific Target Organ Toxicity (Repeated Exposure): Not classified Aspiration Hazard: Not classified

12

ECOLOGICAL INFORMATION

Petroleum gases, liquefied cas#:(68476-85-7)

Information on Ecology Toxicity: No additional information Persistence and Degradability: No additional information available Bioaccumulative Potential ---Solar Chemical Oil Charge 3 Log Pow: < 1 Petroleum gases, liquefied (68476-85-7) Log Pow: 2.3 Mobility in Soil: No additional information available Other Adverse Effects: No additional information available

13 DISPOSAL CONSIDERATIONS

Petroleum gases, liquefied cas#:(68476-85-7)

Information on Disposal

Waste Treatment Methods

Waste Disposal Recommendation: Dispose of waste in accordance with all local, regional, national, provincial, territorial and international regulations. Additional Information: Empty product containers may contain hazardous resideu. Do not reuse empty containers without commercial cleaning or reconditioning.



14

Solar Chemical, inc.

Solar Chemical 1234YF Arctic Air

TRANSPORT INFORMATION

14.1. In Accordance with DOT

Proper Shipping Name: Consumer Commodity, ORM-D 14.2. In Accordance with IMDG Proper Shipping Name: PETROLEUM GASES, LIQUEFIED Hazard Class: 2 Identification Number: UN1075 Label Codes: 2.1 EmS-No. (Fire): F-D EmS-No. (Spillage): S-U Marine Pollutant: No 14.3. In Accordance with IATA Proper Shipping Name: PETROLEUM GASES, LIQUEFIED Identification Number: UN1075 Hazard Class: 2 Label Codes: 2.1 ERG Code (IATA): 10L Marine Pollutant: No



15

REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[--%] Petroleum gases, liquefied (68476-85-7) MASS, OSHAWAC, PA, TSCA, TXAIR

[--%] Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5) NJHS, TSCA This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend

MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TSCA = Toxic Substances Control Act TXAIR = TX Air Contaminants with Health Effects Screening Level NJHS = NJ Right-to-Know Hazardous Substances




16

Solar Chemical, inc.

Solar Chemical 1234YF Arctic Air

SDS

OTHER INFORMATION



Disclaimer: Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Author: Devin Daniels Publication Date: 6/7/2022

Revision Date: 6/7/2022