

Solar Chemical 1234YF Oil Charge

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Solar Chemical 1234YF Oil Charge
Revision Date: 6/7/2022
Version: 1.0
Product Description: Oil Charge for 1234yf A/C systems
Supplier Details: Solar Chemical
 3741 Atlanta Industrial Parkway
 Atlanta, GA 30331
 Office: (404) 699-8766
Contact: Roen Sanders
Phone: (404) 699-8766
Email: solarchem@atlanticchemical.com
Internet: www.solarchemonline.com
Emergency Telephone: Chemtrec 1-800-424-9300 (USA)

2 HAZARDS IDENTIFICATION

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):
 Physical, Flammable Gases, 1
 Physical, Gases Under Pressure, Compressed Gas

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

H220 - Extremely flammable gas
 H280 - Contains gas under pressure; may explode if heated
 OSHA-H01 - May displace oxygen and cause rapid suffocation

GHS Precautionary Statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 P381 - In case of leakage, eliminate all ignition sources.
 P403 - Store in a well-ventilated place.
 P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

3 COMPOSITION/INFORMATION ON INGREDIENTS

	Chemical Ingredients:	
CAS#	%	Chemical Name:
68476-85-7		Petroleum gases, liquefied
8002-05-9		Petroleum oil

Solar Chemical 1234YF Oil Charge

4

FIRST AID MEASURES

- Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Immediately call a POISON CENTER or doctor/physician.
- Skin Contact:** If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.
- Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
- Ingestion:** Do not induce vomiting. Immediately call a poison center or doctor/physician.

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms/Injuries: Gas can be toxic as simple asphyxiant by displacing oxygen from the air. Refrigerated liquefied gas. Contact with product may cause cold burns or frostbite.

Symptoms/Injuries After Inhalation: Asphyxiant gas.

Symptoms/Injuries After Skin Contact: May cause frostbite.

Symptoms/Injuries After Eye Contact: Contact with the liquefied gas causes frostbite.

Symptoms/Injuries After Ingestion: Ingestion is an unlikely route of exposure for a gas.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

5

FIRE FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable gas.

Explosion Hazard: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Contains gas under pressure; may explode if heated. Reacts with strong oxidants causing fire and explosion hazard.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

6

ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe gas.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip clean up crew with proper protection.

Emergency Procedures: Stop Leak if safe to do so. Ventilate area.

6.2. Environmental Precautions

Avoid release to the environment.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Stop leak without risks if possible. Do not take up in combustible material, such as saw dust.

Methods for Cleaning Up: Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

7

HANDLING AND STORAGE

Handling Precautions:

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Personnel should be trained to regularly inspect equipment such as pumps, hoses, and valves. Do not breathe gas. Ensure there is adequate ventilation. Close valve after each use and when empty.

Solar Chemical 1234YF Oil Charge

Open valve slowly to avoid pressure shock.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Storage Requirements:

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Keep at temperatures below 52 °C/125 °F.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep in fireproof place. Store locked up.

Incompatible Products: Heat sources. Oxidizers.

7.3. Specific End Use(s)

Oil for refrigerat A/C units

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Alarm detectors should be used when toxic gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment:

Petroleum gases, liquefied cas#:(68476-85-7)

Gas mask. Protective goggles. Gloves. Protective clothing.

Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear working gloves when handling gas containers.

Eye Protection: Safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: use a NIOSH-approved self-contained breathing apparatus in oxygen deficient atmospheres.

Thermal hazard Protection: Wear cold insulating gloves.

Petroleum gases, liquefied cas#:(68476-85-7)

USA ACGIH - ACGIH TWA (ppm): 1000ppm

USA NIOSH - NIOSH REL (TWA) (mg/m3): 1800mg/m3

USA NIOSH - NIOSH REL (TWA) (ppm): 1000ppm

USA IDLH - US IDLH (ppm): 2100ppm (10% LEL)

USA OSHA - OSHA PEL (TWA) (mg/m3): 1800mg/m3

USA OSHA - OSHA PEL (TWA) (ppm): 1000ppm

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, colorless

Physical State: Gas

Odor Threshold: No data available

Specific Gravity or Density: 0.540

Viscosity: No data available

Boiling Point: - 34.67 °C (- 30.4 °F)

Partition Coefficient: < 1

Vapor Pressure: 70 (@ 21.1 °C)

Odor: No data available

Solubility: No data available

Freezing or Melting Point: - 166.1 °CV (- 267 °F)

Flash Point: No data available

Vapor Density: 1.76 (@ 20C)

Autoignition Temperature: 862.78 °C (1581 °F)

Upper Flammability Limit and Lower Flammability Limit: 8.5 % / 1.9 5

Potentia Hydrogenii: No data available

Evaporation Rate: Rapid

Decompression Temperature: No data available

10

STABILITY AND REACTIVITY

Reactivity: Contains gas under pressure; may explode if heated. Reacts with oxidants causing fire/explosion hazard.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Conditions to Avoid Identification: Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks.

Materials to Avoid Identification: Heat. Strong oxidizers.

Hazardous Decomposition: Carbon oxides (CO, CO2).

Solar Chemical 1234YF Oil Charge

Hazardous Polymerization: Hazardous polymerization will not occur.

11 TOXICOLOGICAL INFORMATION

Petroleum gases, liquefied cas#:(68476-85-7)

Information on Toxicology

Acute Toxicity: Not classified

LC50 Inhalation Rat: 658mg/l/4h

Petroleum Oil: > 2000 mg/kg

LD 50 Oral Rat: > 2000 mg/kg

LD50 Dermal Rat: > 2000 mg/kg

LC50 Inhalation Rat: > 2000 mg/kg

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitiation: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

12 ECOLOGICAL INFORMATION

Petroleum gases, liquefied cas#:(68476-85-7)

Information on Ecology

Toxicity: No additional information

Persistence and Degradability: No additional information available

Bioaccumulative Potential ---

Log Pow: < 1

Petroleum gases, liquefied (68476-85-7)

Log Pow: 2.3

Mobility in Soil: No additional information available

Other Adverse Effects: No additional information available

13 DISPOSAL CONSIDERATIONS

Petroleum gases, liquefied cas#:(68476-85-7)

Information on Disposal**Waste Treatment Methods**

Waste Disposal Recommendation: Dispose of waste in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Empty product containers may contain hazardous residue. Do not reuse empty containers without commercial cleaning or reconditioning.

14 TRANSPORT INFORMATION

14.1. In Accordance with DOT

Proper Shipping Name: Consumer Commodity, ORM-D

14.2. In Accordance with IMDG

Proper Shipping Name: Petroleum gases, liquefied

Hazard Class: 2

Identification Number: UN1075

Label Codes: 2.1

EmS-No. (Fire): F-D

Solar Chemical 1234YF Oil Charge

EmS-No. (Spillage): S-U

14.3. In Accordance with IATA


Proper Shipping Name: Petroleum gases, liquefied

Identification Number: UN1075

Hazard Class: 2

Label Codes: 2.1

ERG Code (IATA): 10L



15

REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[--%] Petroleum gases, liquefied (68476-85-7) MASS, OSHAWAC, PA, TSCA, TXAIR

[--%] Petroleum oil (8002-05-9) MASS, PA, TSCA, TXHWL

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend

MASS = MA Massachusetts Hazardous Substances List

OSHA = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level

TXHWL = TX Hazardous Waste List

16

OTHER INFORMATION



Disclaimer: Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Author: Devin Daniels

Publication Date: 6/7/2022

Revision Date: 6/7/2022